

DECLARATION OF PERFORMANCE



ROOF WALKWAY class 2



Unique identification code of the product-type:

Orima® Roof walkway

Name	Product code	Installation guide	Name	Product code	Installation guide
Roof walkway 2,97 m	30030	KS3C2, KS4C2, KS4HC2, KS7C2,	Lower supporter	31050	KS8C2, KS8DC2 KS8C2 ETUTUKI
Roof walkway 2,25 m	30200	KS7WC2 KS8C2, KS8AC2, KS8BC2,	Front support to brick roof fastener	31680	KS8C2 ETUTUKI
Roof walkway 1,21 m	30010	KS8DC2, KS8C2	Fastener	30780	KS8AC2, KS8BC2
Upper supporter	30060	ETUTUKI, KS9C2,	Fastener	30790	KS8AC2, KS8BC2
Sideway support	35110	KS9WC2	Fastener (batten)	30810	KS8AC2
Seam fastener set	35820	KS3C2	Fastener (board)	30800	KS8BC2
Roof fastener	30630	KS4C2, KS4HC2	Roof fastener	30820	KS8DC2
Lower supporter profile	30530	KS7C2	Batten support	30830	KS8DC2
Roof fastener, 3 hole	30770	KS7WC2	Lower supporter	30120	KS9C2, KS9WC2
Fastener W-20	34330	KS7WC2	Lower supporter	30130	KS9C2
Fastener W-45J/900	34340	KS7WC2			

Intended use of building product

Roof access (building products) permanently fixed to the load-bearing construction of pitched roofs, to stand or to walk on during inspection, maintenance and repair of facilities on the roof. Class 2 installations may be used as anchorage points for personal fall protection equipment.

Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila
+358 3 872 100, www.orima.fi, myynti@orima.fi

System of assessment and verification of constancy of performance of the construction product

System 3 (AVCP-class)

Notified body

VTT Expert Services Oy (nr 0809) performed the type of product testing according to SFS-EN 516:2006 Class 2 Type B under system 3 and issued test reports.

Declared performance

Walkway type B, width 350 mm (acc. 6.2)

Essential characteristics	Performance	Harmonized technical specification
Mechanical strength	Static load according to 7.1, class 2	SFS-EN 516: 2006
	Fatigue strength according to 7.2, class 2	
Reaction to fire	A1	
External fire performance	B _{roof}	
Durability	Corrosion resistance equivalent to hot-galvanised steel	

The performance of the product identified in this document is conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 6.6.2018

Mikko Ahonen, CEO