

# DECLARATION OF PERFORMANCE



## ROOF FENCES

### Unique identification code of the product-type:

Orima® Roof fences

Name	Product code	Installation guide
Oval tube 3,0 m	31010	SYP, SYPL, SYV, SYVL, SYO, SYOL, SYT, SYTL, SYS, SYSL, SYR, SYRL, SYN, SYNL
Lower supporter profile	30530	SYT, SYTL, SYV, SYL
Vertical support 0,50 m	33490	SYT, SYTL, SYV, SYVL, SYR, SYRL
Diagonal support 0,80 m	33480	SYT, SYTL, SYV, SYVL, SYR, SYRL
Lower supporter	30070	SYO, SYOL, SYV, SYVL
Diagonal support 1,10 m	33440	SYO, SYOL, SYS, SYSL, SYN, SYNL
Vertical support 0,95 m	33460	SYO, SYOL, SYS, SYSL, SYN, SYNL
Console	33470	SYP, SYPL
D-loop	20530	SYP, SYPL
Seam fastener set	35640	SYN, SYNL, SYR, SYRL
Seam fastener	22170	SYN, SYNL, SYR, SYRL

### Intended use of building product

Horizontal barrier permanently fixed to the construction of pitched roofs, prevents a person from falling off the roof.

### Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila  
+358 3 872 100, [www.orima.fi](http://www.orima.fi), [myynti@orima.fi](mailto:myynti@orima.fi)

**Product testing** Roof fences are tested according to GOST R 53254-2009. There is not a harmonised standard for roof fences and therefore cannot be CE marked.

### Declared performance

Essential characteristics	Performance	Standard
Mechanical strength	Static strength: Horizontally load 0,54 kN according to 6.2.15	GOST R 53254-2009
Dimensions	according to the table G.1	

The performance of the product identified in this document is conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 15.6.2018

Mikko Ahonen, CEO